

Declaration of Compliance

This declaration applies to all below mentioned products manufactured by Deca

Products concerned

All transparent RCP-articles. These products consist out of 100% virgin materials and are 100% recyclable
This article is made with monolayer polypropylene, and therefore cannot be considered as a functional barrier. Though it might delay
migration from sources from outside of the packaging, it will not prevent it 100,00%. Factors such as the source of the outside
contamination (e.g. recycled shipper vs spilled mineral oil), time (e.g. 2 weeks vs a year) and temperature (e.g. 10°C vs 40°C) have to
be taken into consideration. DECA is not responsible for any contiminatants that the costumer might put the packaging into contact with.

Legislation

The articles supplied comply with the legal regulations

HPP - plastic

- Regulation (EU) No 10/2011 on plastic materials and articles intended to come into contact with food including amendments
- The food ingredients listed in Annex II of Regulation (EU) No 1169/2011, are not used in the manufacturing of or formulation of these products. However, this has not been tested for these substances.
- Regulation No. 1895/2005 on the use of BADGE, BFDGE and NOGE.
- Regulation (EC) No 1907/2006 (REACH). It is assured that none of the substances of very high concern (SVHC) within the
 meaning of Regulation No 197/2006 are contained above 0.1%. Substances as listed in the currently valid list "Candidate List
 of Substances of very High Concern".
- Regulation (EC) 1935/2004 of the European parliament and of the council of 27/10/2004 on materials and articles intended to come into contact with food and repealing Directives 80/590/EEC and 89/109/EEC
- Regulation (EC) No 2023/2006, On good manufacturing practice (GMP) for materials and articles intended to come into contact with food.
- Guideline 94/62/EC on packaging and packaging waste.
- FDA 21 CFR 177.1520 (olefin polymers)
- Nanomaterials are not used in the manufacture or the formulation of this product. The statement is based on information of raw material suppliers and approved internally by GMP. However, it has not been tested for these substances.
- Phthalates are not used in the manufacture or the formulation of this product. The statement is based on information of raw material suppliers and approved internally by GMP. However, it has not been tested for these substances.

Specification on the use of the articles (food types)

- Dry products
- Aqueous products pH > 4,5
- Acid products Ph ≤ 4,5
- Alcoholic products ≤ 6% vol
- Fatty products



Migration data

Overall Migration (OM)

Simulant	Food type	Test conditions	Maximum customer / consumer conditions of use	Surface/volume ratio applied during migration test	Result
А	Aqueous products, pH > 4,5	2 hours at 100°C or 1 hour at 121°C	High temperature applications up to 121 °C.	1 dm²/100 ml	< 10 mg/dm ²
В	Acid products, pH ≤ 4,5	2 hours at 100°C or 1 hour at 121°C	High temperature applications up to 121 °C.	1 dm²/100 ml	< 10 mg/dm ²
D2	Fatty products		Any long-term storage at room temperature or below, including when packaged under hot-fill conditions, and/or heating up to a temperature T where 70 °C \leq T \leq 100 °C for a maximum of t = 120/2 $^{(T-70)/10)}$	1 dm²/100 ml	< 10 mg/dm ¹

The intended amount of maximum food contact surface area of individual articles can be found on their respective technical datasheets. The relative food contact surface area between the food and the packaging is managed by the customer (e.g. rice vs an apple).

Specific Migration Limits (SML)

The underneath data is based on supplier data and confirmed through migration tests. Migration tests on SML's are performed with simulants who lead to the worst-case scenarios specific to the chemical.

Substance	FCM	CAS	SML	Origin		
1,3,5-Tris(3,5-Di-Tert-Butyl-4-Hydroxybenzyl)-1,3,5-Triazine-2,4,6(1H,3H,5H)-Trione	661	27676-62-6	5 mg/kg	RCP		
2,5-Bis(5-Tert-Butyl-2-Benzoxazolyl)Thiophene	500	7128-64-5	0,6 mg/kg	RCP		
9,9-Bis (Methoxymethyl)-9H-Fluorene	779	182121-12-6	0.05 mg/kg	RCP		
Aluminium		7429-90-5	1 mg/kg	RCP		
Atmer	19 + 20		1,2 mg/kg	RCP		
Bis(4-Propylbezylidene)-Propylsorbitol	808	882073-43-0	5 mg/kg	RCP		
Octadecyl 3-(3,5-Di-Tert-Butyl-4-Hydroxyphenyl)Propionate)	433	2082-79-3	6 mg/kg	RCP		
Zinc	-	7440-66-6	5 mg/kg	RCP		

Dual Use Additives (additives with a limitation in food)

Substance	E- nr	FCM	REF	CAS	Origin
Mono- And Diglycerides Of Fatty Acids	E471	-	-	123-94-4	RCP
Sodium, Potassium And Calcium Salts Of Fatty Acids	E470a	9	30610	1592-23-0	RCP

Storage conditions and expiration of unused products

Recommended storage conditions are

- Closed, in the original packaging
- Dry
- Out of direct sunlight
- At ambient temperatures
- At relative humidity between 40 and 70%

We recommend to use the products within 1 year after purchase. We cannot be held responsible for use after this period.

Processing conditions

- Heating: For articles without IML, the temperatures used in heating processes may not exceed the conditions of the migration tests (e.g. hot fill, pasteurization, reheating in microwave).
- Freezing: Cold temperatures cause no issues in matters regarding food safety. However, articles might be sensitive to impact when cooled (dependent on the temperature and the nature of the production/transport process). It is the costumer's responsibility to test the articles for practical functionality within his process.

Non-conformities

Acceptable quality limit



DECA considers three types of non-conformities. Depending on the nature of the non-conformity, another AQL is considered.

Defect nature	Severity	AQL
Acute food safety risks	Critical	0
Functionality risks	Major	2.5
Esthetical risks	Minor	4.0

Complaints

In order to enable DECA to thoroughly process complaints at the quickest rate, DECA requests that the costumer shares the following: information

- A description of the defect (with pictures to illustrate the defect)
- Batch number (advice: mail a picture of the shipper/pallet label to DTE)
- Pallet numbers / shipper numbers (advice: mail a picture of the shipper/pallet to DTE)
- Amount of defect
- Samples of the defect
- · Whether information is available on which cavity numbers the defect occurs

Disclaimer

This declaration is given in good faith and to the best of our current knowledge. It should be noted that when the product is further processed, that our customer has the sole responsibility to determine

- That the use delivered is lawful and safe according to the information given in this document
- The product is technically suitable so that no change in flavor, taste or organoleptic properties occur

We therefore advise extensive testing of our products in the production environment of our customer. This declaration is only valid if

- The articles delivered are processed according to good manufacturing practice and to our technical specifications
- The articles are not altered by other detrimental processes

This document is valid 2 years after publication.

Vojens d. 06.05.2024 Dansk Transport Emballage A/S

Michael Gabelgaard Minke QM